Data Sheet



2SRM-AC Two Single Relay Module, AC Signal Input

Description

The 2 SRM-AC Module is intended for use with Direct Digital Controllers to convert two Digital Output Triacs into two Relay Switching Outputs.

The 2 SRM-AC Module is constructed on a Epoxy Glass Laminate and housed in an industry standard 80mm DIN Rail Mounting. Generous 2.5mm² terminals are provided for the field interconnections.

The 2 SRM-AC Module is CE rated and is RoHS compliant.



Applications

Applications include the switching via Relay contacts of any Plant up to a 10Amp resistive load.

Converting low power Triac or Relay type Digital Outputs to Relay operation.

To provide Local Manual Control of the Plant in case of controller failure.

Local Manual Control of the Plant will also enable pre-commissioning and testing.

To provide a Local LED indication of Output Status.

To provide isolation of the controller from the Harsh Plant Environment, protecting the Controller.

The inputs are suited to controllers with Triac outputs.

Features

Provides 2 SPDT Relay Output channels C/NO/NC

Auto/On/Off jumper for plant checkout and override.

LED status indication.

Design for DIN rail mounting. Rising cage Terminals.

Flame retardant Polyamide DIN mounting.

A remote Auto/On/Off Switch is available.

2 SRM-AC Data Sheet. Issue 2, Jan 2010 E&OE.

Supplied By



Page 1 of 2

Specifications

Input Signal:	2 x Triac or Relay closure to common (0V).		
Output Contacts:	10 Amp @ 230V AC Resistive. S.P.D.T.		
Power Supply:	24V AC @ 1 VA (+/-15%)		
LED Indication:	ON when relay energised.		
Output States:	Jumper selectable AUTO/ON/OFF. Auto, controlled by input. On, always on. Off, always off.		
Electrical connections: Ambient Conditions: Dimensions: Weight I.P. Rating: Mounting	Rising cage terminals for 0,5 to 2,5mm ² cable. -10 to 50°C 0 to 80% RH non-condensing. 80 x 45 x 52mm. 80g IP00. Flame retardant green Polyamide 66 UL 94V0 moulding. To suit 35mm top hat din rail.		

Switching Table

Input A	Relay A	Input B	Relay B
	OFF	Open	OFF
Closed	ON	Closed	ON

Inputs are closed to the common 0V terminal via the Triac or Relay.

See also the 2 SRM-AC Installation Sheet for wiring detail.

Page 2 of 2

Watchtower Trading reserves the right to update this product, revise and update this publication including information hereof without obligation to notify any person of such updates, revisions or changes.

Watchtower Trading

PO Box 950, Bromhof, 2154. Telephone +27 11 886 5943 Fax +27 11 886 5947

www.watchtower.co.za Email: watchtower@icon.co.za